

### Product Characteristics

- Prevents lifting & bleeding of existing paint coating
- Protects against solvent attack
- Does not require sanding
- Can be over coated with all types of single & 2 pack topcoats
- Quick drying.
- Ready For Use

### Physical and chemical

|  |   |
|--|---|
| Product Type   | High Grade Resin  |
| Colour   | Yellow oxide  |
| Coverage   | 10m <sup>2</sup> per Litre  |
| Temperature resistance to 90 °C  |   |
| Storage stability  | Dust free 10-15 minutes. Touch dry 30 minutes. Over coatable after 3 hours. Apply the first paint layer in a light coat |
| The drying time depends on temperature, humidity & the thickness of the applied coat |   |

### Surface Preparation

- The surface must be free from all contamination, including rust, grease & moisture
- To achieve sufficient protection, apply 1-2 light coats



#### DISCLAIMER OF LIABILITY

The information contained in this Technical Data Sheet is correct to the best of Alpha Coatings Limited trading as Capella Solutions Group's ("Capella") knowledge, however, you must satisfy yourselves that the Goods are suitable for your needs by way of your independent testing or other processes. Capella makes no warranty, representation, or guarantee regarding the information contained in the Technical Data Sheet or the suitability of its products and services for any particular purpose, nor does Capella assume liability arising out of the application or use of the Goods other than any liability which cannot be limited by law including but not limited to liability for: (a) death or personal injury caused by negligence; (b) fraud or fraudulent misrepresentation; and (c) breach of the terms implied by section 12 of the Sales of Goods Act 1979, in such circumstances Capella's total liability shall not exceed the cost of the Goods. Capella's total liability includes liability in contract, tort, negligence, breach of statutory duty, or otherwise. It is the Customer's responsibility to ensure that the guidance on the Technical Data Sheet is followed.