

Paint Rocket additive is for use with 2K isocyanate hardeners to accelerate the curing time in low environmental temperatures. It is suitable to be used with most 2K paint systems.

### Features and benefits

- Speeds up curing time from between 30-50%
- Suitable for use with most 2K paint systems
- Decreases total workshop time

### Physical and chemical

<b>Colour:</b>	Clear
<b>Specific Gravity:</b>	0.882
<b>Sizes:</b>	250ml & 500ml
<b>Storage:</b>	Product should be stored in original container, protected from heat sources, at a temperature range between + 5°C & + 35°C
<b>Shelf Life:</b>	Stored under the above conditions the product has a stability of 48 months from production date.
<b>VOC: (volatile organic compound)</b>	<b>VOC (Directive 2010/75/EC): 95%-899.65 Grams/Litre</b> <b>VOC: 56.93% - 539.08 Grams/Litre</b>

### Mixing guide

Mix ProXL Paint Rocket directly with your isocyanate hardener, add between 10 and 30ml per litre of hardener (1-3%). Once the Paint Rocket is added to your hardener, shake well before adding to your paint.

### Directions for use



1) Loosen chamber cap and squeeze

2) Remove cap and pour exact measure

Loosen the cap and gently squeeze the filled dispenser bottle with one hand, filling the dosing chamber to the required amount. The cap is then removed allowing the measured amount to be dispensed with ease.

### Warnings

ProXL Paint Rocket should only be used with slow, standard or fast hardeners, but should never be added to extra-fast hardeners.

If an excessive ratio of ProXL Paint Rocket is used, or if used in too warm an environment, there could be a reduction of gloss level in the finished surface.

### Environmentally sound

The products supplied by ProXL are 100% free of heavy metals and the caps and packaging are made of recyclable material.

### Disposal

Completely emptied cans should be put in recycling skips or appropriate container. Cans which are not empty should be disposed off as special refuse.

This application and technical information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively is the responsibility of the user.



#### DISCLAIMER OF LIABILITY

The information contained in this Technical Data Sheet is correct to the best of Alpha Coatings Limited trading as Capella Solutions Group's ("Capella") knowledge, however, you must satisfy yourselves that the Goods are suitable for your needs by way of your independent testing or other processes. Capella makes no warranty, representation, or guarantee regarding the information contained in the Technical Data Sheet or the suitability of its products and services for any particular purpose, nor does Capella assume liability arising out of the application or use of the Goods other than any liability which cannot be limited by law including but not limited to liability for: (a) death or personal injury caused by negligence; (b) fraud or fraudulent misrepresentation; and (c) breach of the terms implied by section 12 of the Sales of Goods Act 1979, in such circumstances Capella's total liability shall not exceed the cost of the Goods. Capella's total liability includes liability in contract, tort, negligence, breach of statutory duty, or otherwise. It is the Customer's responsibility to ensure that the guidance on the Technical Data Sheet is followed.