



ProCut

Size 1kg & 250g Code: PCG20-1



Procut is a single-stage, high-performance cutting compound that has been specifically developed for the refinisher and detailer, removing severe paint defects in seconds and resulting in a high gloss finish.

- Polishes P1200-1500
- Extremely fast cut
- Single-stage compound and polish
- Zero VOC content
- Long working time with very low dust
- Zero fillers

Physical	Properties
-----------------	-------------------

,					
Physical state:	Paste	Ignition temperature in °C:	>200		
Colour:	White/transparent when used				
		VOC content:	Zero (0.0g/l)		
Odour:	Odourless	Shelf life:	2 years		
Flashpoint:	130°C	Storage temp:	15°C-25°C		

ProFinish

Size 1kg & 250g Code: PFG20-1

PFG20-250



ProFinish guarantees a perfect gloss finish on all colours, including difficult dark colours. This unique polish formulation is based on a microfine, high purity aluminium oxide powder that quickly and easily eliminates any swirl marks, holograms or light scratches from the final coating.

The Hard Compound Pad has been specially developed in conjunction with Procut Extreme Cut

- **Excellent for dark colours**
- Extremely high gloss
- Hologram free finish
- Zero fillers

Physical	Prop	erties
riiyəicai	ГІОР	CI LICS

Physical state:	Liquid	Ignition temperature ig °C:	>200
Colour:	White/transparent when used		
		VOC content:	135 g/l
Odour:	Characteristic	Shelf life:	2 years
Flashpoint:	61°C	Storage temp:	15°C-25° <u>C</u>

Hard Compound Pad

Pack of 2 Code: HPG20-150/2



Compound.

- 3D crosscut technology
- Enhanced cutting performance
- Intelligent heat regulation

Open-cell foam

Medium Polish Pad

The Medium Polish Pad as been specially developed in conjunction with both Procut Extreme Cut Compound and the Generation 20 ProFinish Polish.

- Suitable for both compound and polishing
 - Recommended pad for the ProFinish Polish
 - Central hole to reduce heat

Open-cell foam Size: 140mm

Pack of 2 Code: MPG20-150/2





Application	EXTREME CUT Single-stage compound and polish to easily remove P1200-P1500 flatting marks resulting in a high-gloss finish	MEDIUM CUT Single-stage compound to quickly remove scratches and marks from new and old paintwork resulting in a high- gloss finish	FINAL POLISH Final finish polish to be used in conjunction with the previous two applications for a superior high-gloss and hologram free finish, especially for dark colours	
Compound or Polish	ProCut	ProCut	ProFinish	
Recommended Pad	Hard Compound Pad	Medium Polish Pad	Medium Polish Pad	
Process	Use a small amount of ProCut spread evenly on the Hard Compound Pad. 1st pass with polisher at 1000 rpm then increase speed to 1500-2000 rpm. Wipe off with microfibre cloth	Use a small amount of ProCut spread evenly on the Medium Polish Pad. 1st pass with polisher at 1000 rpm then increase speed to 1500 rpm. Wipe off with microfibre cloth	Use a small amount of ProFinish spread evenly on the Medium Polish Pad. 1st pass with polisher at 1000 rpm then increase speed to 1500 rpm. Wipe off with microfibre cloth	
Main Benefits	 No need to use finer than P1500 discs Super-fast process Only needs one product 	 Super-fast process Only needs one product 	 Superior high-gloss finish Eliminates come-back with holograms on dark colours 	