

ProZINC Size 500ml

Code: PROZINC

PROZINC provides excellent adhesion and corrosion prevention. Quick drying. Formulated for refinishing of OEM plated zinc-coated car bodies.

Suitable substrates (cleaned & abraded)

Galvanised Steel

Physical and chemical data

Basis of binder	Special Mix of Resin
Colour	Grey
Coverage	1.2m²
Temperature resistance	Up to 90°C
Storage stability	Empty cans 36 month. Relative air humidity of max. 60%)
Size	500ml
VOC content	340 g/500ml

Application guide

- · Carry out test spray
- · Areas to be sprayed must be free of grease, dust and dry
- · For professional use only
- Wear an appropriate respirator



Before use, shake the aerosol for 2 minutes and spray a sample area.



Apply in cross coats from distance of 250mm from object



Apply 2 light coats from a distance of 250mm



Allow 5-10 minutes of flash off between coats.



5-8 Minutes



After use, turn aerosol upside down and empty valve

Features and benefits

- Fast drying
- Excellent corrosion protection
- High adhesion on zinc coated surfaces
- Supplied with 2 nozzles

Environmentally sound

The products supplied by ProXL are 100% free of heavy metals and the caps and packaging are made of recyclable material.

Disposal

Completely emptied cans should be put in recycling skips or appropriate container. Cans which are not empty should be disposed off as special refuse.

This application and technical information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively is the responsibility of the user.

