

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 22.04.2015

Revision: 22.04.2015

1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier** ADTMSG
- **Trade name:** INDURA - UHS DTM HIGH GLOSS ACRYLIC VOC COMPLIANT
- **Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:** Capella Solutions Group , Second Avenue , Chatham , Kent
Tel: +44 (0)1634 823900 **Email:** sales@capellasolutionsgroup.com
Further information obtainable from: Product safety department
- **Emergency telephone number:** Tel: +44(0) 1634 823900 (08.00 / 17.00)
uK: NPIS National Poisons Information Centre Tel: +44 0344 892 0111
IRL: Beaumont Hospital - National Poisons Information Centre: Tel: +353 1 8092566

2 Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Xi; Sensitising

R43: May cause sensitisation by skin contact.

R10-52/53-67: Flammable. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Vapours may cause drowsiness and dizziness.

- **Information concerning particular hazards for human and environment:**
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
- **Classification system:**
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- **Label elements**

- **Labelling according to EU guidelines:**
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 22.04.2015

Revision: 22.04.2015

Trade name: INDURA - UHS DTM HIGH GLOSS ACRYLIC VOC COMPLIANT

(Contd. of page 1)

· **Code letter and hazard designation of product:**



Xi Irritant

· **Hazard-determining components of labelling:**

bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate

· **Risk phrases:**

10 Flammable.

43 May cause sensitisation by skin contact.

52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

67 Vapours may cause drowsiness and dizziness.

· **Safety phrases:**

2 Keep out of the reach of children.

24/25 Avoid contact with skin and eyes.

29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. INDURA - UHS DTM HIGH GLOSS ACRYLIC VOC COMPLIANT

37 Wear suitable gloves.

46 If swallowed, seek medical advice immediately and show this container or label.

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterisation: Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 123-86-4 EINECS: 204-658-1	n-butyl acetate R10-66-67 ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	10-25%
CAS: 110-43-0 EINECS: 203-767-1	heptan-2-one ⚠ Xn R20/22 R10 ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332	10-25%

(Contd. on page 3)

GB









Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 22.04.2015

Revision: 22.04.2015

Trade name: INDURA - UHS DTM HIGH GLOSS ACRYLIC VOC COMPLIANT

(Contd. of page 2)

CAS: 1330-20-7 EINECS: 215-535-7	xylene  R10 	2.5-10%
CAS: 100-41-4 EINECS: 202-849-4	ethylbenzene  	≤ 2.5%
CAS: 41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate  	≤ 2.5%
CAS: 67-56-1 EINECS: 200-659-6	methanol  	≤ 2.5%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- **Description of first aid measures**
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

GB

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 22.04.2015

Revision: 22.04.2015

Trade name: INDURA - UHS DTM HIGH GLOSS ACRYLIC VOC COMPLIANT

(Contd. of page 3)

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

123-86-4 n-butyl acetate

WEL	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
-----	---

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 22.04.2015

Revision: 22.04.2015

Trade name: INDURA - UHS DTM HIGH GLOSS ACRYLIC VOC COMPLIANT

(Contd. of page 4)

110-43-0 heptan-2-one

WEL Short-term value: 475 mg/m³, 100 ppm
Long-term value: 237 mg/m³, 50 ppm
Sk

1330-20-7 xylene

WEL Short-term value: 441 mg/m³, 100 ppm
Long-term value: 220 mg/m³, 50 ppm
Sk; BMGV

100-41-4 ethylbenzene

WEL Short-term value: 552 mg/m³, 125 ppm
Long-term value: 441 mg/m³, 100 ppm
Sk

67-56-1 methanol

WEL Short-term value: 333 mg/m³, 250 ppm
Long-term value: 266 mg/m³, 200 ppm
Sk

· **Ingredients with biological limit values:**

1330-20-7 xylene

BMGV 650 mmol/mol creatinine
Medium: urine
Sampling time: post shift
Parameter: methyl hippuric acid

· **Additional information:** The lists valid during the making were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 22.04.2015

Revision: 22.04.2015

Trade name: INDURA - UHS DTM HIGH GLOSS ACRYLIC VOC COMPLIANT

(Contd. of page 5)

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· Form:	Liquid
· Colour:	Whitish
· Odour:	Characteristic
· Odour threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	151 °C

· **Flash point:** 41 °C

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 370 °C

· **Decomposition temperature:** Not determined.

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

· Lower:	1.0 Vol %
· Upper:	7.5 Vol %

· **Vapour pressure at 20 °C:** 10.7 hPa

· **Density at 20 °C:** 1.02 g/cm³

· **Relative density** Not determined.

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 22.04.2015

Revision: 22.04.2015

Trade name: INDURA - UHS DTM HIGH GLOSS ACRYLIC VOC COMPLIANT

(Contd. of page 6)

· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	42.1 %
VOC (EC)	42.10 %
· Solids content:	64.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values relevant for classification:**

110-43-0 heptan-2-one

Oral	LD50	1670 mg/kg (rat)
Dermal	LD50	12600 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitisation:** Sensitisation possible through skin contact.
- **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 22.04.2015

Revision: 22.04.2015

Trade name: INDURA - UHS DTM HIGH GLOSS ACRYLIC VOC COMPLIANT

Irritant

(Contd. of page 7)

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Harmful to aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|----------------------------------|------------|
| · UN-Number | |
| · ADR, IMDG, IATA | UN1263 |
| · UN proper shipping name | |
| · ADR | 1263 PAINT |
| · IMDG, IATA | PAINT |

(Contd. on page 9)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 22.04.2015

Revision: 22.04.2015

Trade name: INDURA - UHS DTM HIGH GLOSS ACRYLIC VOC COMPLIANT

(Contd. of page 8)

· **Transport hazard class(es)**· **ADR, IMDG, IATA**

· **Class** 3 Flammable liquids.
· **Label** 3

· **Packing group**· **ADR, IMDG, IATA** III· **Environmental hazards:**· **Marine pollutant:** No· **Special precautions for user** Warning: Flammable liquids.· **Danger code (Kemler):** 30· **EMS Number:** F-E, S-E

· **Transport in bulk according to Annex II of
MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**· **ADR**· **Limited quantities (LQ)** 5L· **Transport category** 3· **Tunnel restriction code** D/E· **IMDG**· **Limited quantities (LQ)** 5L· **Excepted quantities (EQ)** Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· **UN "Model Regulation":** UN1263, PAINT, 3, III

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

No further relevant information available.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 22.04.2015

Revision: 22.04.2015

Trade name: INDURA - UHS DTM HIGH GLOSS ACRYLIC VOC COMPLIANT

(Contd. of page 9)

· **Relevant phrases**

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H370	Causes damage to organs.
R10	Flammable.
R11	Highly flammable.
R20	Harmful by inhalation.
R20/21	Harmful by inhalation and in contact with skin.
R20/22	Harmful by inhalation and if swallowed.
R23/24/25	Toxic by inhalation, in contact with skin and if swallowed.
R38	Irritating to skin.
R39/23/24/25	Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.
R43	May cause sensitisation by skin contact.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

· **Department issuing MSDS:** Environment protection department.

· **Contact:** Mr. Roberts

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 3: Acute toxicity, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

STOT SE 1: Specific target organ toxicity - Single exposure, Hazard Category 1

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3