



ALU ZINC

Size 500ml

Code: AZ500

Products Characteristics

- · Excellent corrosion prevention
- Heat-resistant up to 250°c
- · Fast drying with good spraying properties and good coverage
- · Excellent adhesion and is spot weldable
- · Resistant to petrol, chemicals and external elements

Physical and chemical data

Product Type	Epoxyester
Coverage	1.56 - 2.19m² per 500ml
Drying times	Dust Free 15 minutes Touch Dry 20 - 30 minutes Overcoatable after 24 hours
The drying time depends on temperature, humidity and the thickness of the applied coat.	

Surface Preparation

- The surface must be free from all contamination including rust, grease and moisture.
- Before use, carefully read and note the warning text on the label
- Before application, ensure that the mixing balls in the aerosol are moving freely as this ensures that the zinc content is being physically mixed into the paint.

Environmentally sound

The products supplied by ProXL are 100% free of heavy metals and the caps and packaging are made of recyclable material.

Disposal

Completely emptied cans should be put in recycling skips or appropriate container. Cans which are not empty should be disposed off as special refuse.

This application and technical information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively is the responsibility of the user.

