

GUIDE COAT

Size 500ml

Code: GC500

Products Characteristics

- Easy in use
- Fast drying

Physical and chemical data

Product Type	Nitro-cellulose binder
Coverage	3 to 4 m ²
The drying time dep	ends on temperature, humidity and the

Surface Preparation

· The surface should be clean, dry and free of grease.

Treatment

- The aerosol should have room temperature. Best processing temperature 15 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 cm.
- Apply a thin layer of sanding aid and allow to dry. Sand the surface till the control guide coat is completely removed.
- After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).
- The drying time depends on the ambient temperature, the humidity of the air and the thickness of the coat applied.

Environmentally sound

The products supplied by ProXL are 100% free of heavy metals and the caps and packaging are made of recyclable material.

Disposal

Completely emptied cans should be put in recycling skips or appropriate container. Cans which are not empty should be disposed off as special refuse.

This application and technical information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively is the responsibility of the user.

