

**Section 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier****Product name:** CELLULOSE THINNER**Product code:** T96**1.2. Relevant identified uses of the substance or mixture and uses advised against****1.3. Details of the supplier of the safety data sheet****Company name:** Capella Solutions Group

Second Avenue

Luton

Chatham

Kent

ME4 5AU

United Kingdom

**Tel:** 01634 823900**Fax:** 01634 813807**Email:** sales@capellasolutionsgroup.com**1.4. Emergency telephone number****Emergency tel:** 01634 823900

(office hours only)

UK: NPIS National Poisons Information Centre Tel: +44 0344 892 0111

IRL: Beaumont Hospital - National Poisons Information Centre: Tel: +353 1 8092566

**Section 2: Hazards identification****2.1. Classification of the substance or mixture****Classification under CLP:** Flam. Liq. 2: H225; Eye Dam. 1: H318; Repr. 2: H361d; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H336; -: EUH066**Most important adverse effects:** Repeated exposure may cause skin dryness or cracking. Highly flammable liquid and vapour. Causes skin irritation. Causes serious eye damage. May cause drowsiness or dizziness. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure.**2.2. Label elements****Label elements:****Hazard statements:** EUH066: Repeated exposure may cause skin dryness or cracking.

H225: Highly flammable liquid and vapour.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H336: May cause drowsiness or dizziness.

# SAFETY DATA SHEET

## CELLULOSE THINNER

Page: 2

H361d: Suspected of damaging the unborn child.

H373: May cause damage to organs through prolonged or repeated exposure.

**Hazard pictograms:** GHS02: Flame

GHS05: Corrosion

GHS07: Exclamation mark

GHS08: Health hazard



**Signal words:** Danger

**Precautionary statements:** P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241: Use explosion-proof electrical/ventilating/lighting/.. equipment.

P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+352: IF ON SKIN: Wash with plenty of water/.

P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

### 2.3. Other hazards

**Other hazards:** In use, may form flammable / explosive vapour-air mixture.

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

##### ACETONE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
200-662-2	67-64-1	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	10-30%

##### TOLUENE

203-625-9	108-88-3	-	Flam. Liq. 2: H225; Repr. 2: H361d; Asp. Tox. 1: H304; STOT RE 2: H373; Skin Irrit. 2: H315; STOT SE 3: H336	10-30%
-----------	----------	---	--	--------

##### N-BUTYL ACETATE

204-658-1	123-86-4	-	Flam. Liq. 3: H226; STOT SE 3: H336; -: EUH066	10-30%
-----------	----------	---	--	--------

[cont...]

# SAFETY DATA SHEET

## CELLULOSE THINNER

Page: 3

### ETHANOL

200-578-6	64-17-5	Substance with a Community workplace exposure limit.	Flam. Liq. 2: H225	1-10%
-----------	---------	--	--------------------	-------

### BUTAN-1-OL

200-751-6	71-36-3	-	Flam. Liq. 3: H226; Acute Tox. 4: H302; STOT SE 3: H335; Skin Irrit. 2: H315; Eye Dam. 1: H318; STOT SE 3: H336	1-10%
-----------	---------	---	---	-------

### ISOBUTANOL

201-148-0	78-83-1	-	Flam. Liq. 3: H226; Acute Tox. 4: H302; STOT SE 3: H335; Skin Irrit. 2: H315; Eye Dam. 1: H318; STOT SE 3: H336	1-10%
-----------	---------	---	---	-------

### 4-METHYLPENTAN-2-ONE

203-550-1	108-10-1	-	Flam. Liq. 2: H225; Acute Tox. 4: H332; Eye Irrit. 2: H319; STOT SE 3: H335; -: EUH066	1-10%
-----------	----------	---	--	-------

### M-XYLENE

203-576-3	108-38-3	-	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315	1-10%
-----------	----------	---	---	-------

### ETHYL METHYL KETONE

201-159-0	78-93-3	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	1-10%
-----------	---------	---	--	-------

### P-XYLENE

203-396-5	106-42-3	-	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315	1-10%
-----------	----------	---	---	-------

### ETHYLBENZENE

202-849-4	100-41-4	-	Flam. Liq. 2: H225; Acute Tox. 4: H332; STOT RE 2: H373; Asp. Tox. 1: H304	1-10%
-----------	----------	---	--	-------

### O-XYLENE

202-422-2	95-47-6	-	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315	1-10%
-----------	---------	---	---	-------

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

[cont...]

# SAFETY DATA SHEET

## CELLULOSE THINNER

Page: 4

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Eye bathing equipment should be available on the premises.

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS.

[cont...]

# SAFETY DATA SHEET

CELLULOSE THINNER

Page: 5

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.  
Do not handle in a confined space. Avoid the formation or spread of mists in the air.  
Smoking is forbidden. Use non-sparking tools.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area.  
Ensure lighting and electrical equipment are not a source of ignition.

### 7.3. Specific end use(s)

**Specific end use(s):** No data available.

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Hazardous ingredients:**

**ACETONE**

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1210 mg/m3	3620 mg/m3	-	-

**TOLUENE**

UK	191 mg/m3	384 mg/m3	-	-
----	-----------	-----------	---	---

**N-BUTYL ACETATE**

UK	724 mg/m3	966 mg/m3	-	-
----	-----------	-----------	---	---

**ETHANOL**

UK	1920 mg/m3	-	-	-
----	------------	---	---	---

**BUTAN-1-OL**

UK	-	154 mg/m3	-	-
----	---	-----------	---	---

**ISOBUTANOL**

UK	154 mg/m3	231 mg/m3	-	-
----	-----------	-----------	---	---

**4-METHYLPENTAN-2-ONE**

UK	208 mg/m3	416 mg/m3	-	-
----	-----------	-----------	---	---

**M-XYLENE**

EU	221 mg/m3	442 mg/m3	-	-
----	-----------	-----------	---	---

[cont...]

# SAFETY DATA SHEET

CELLULOSE THINNER

Page: 6

## ETHYL METHYL KETONE

UK	600 mg/m3	899 mg/m3	-	-
----	-----------	-----------	---	---

## P-XYLENE

EU	221 mg/m3	442 mg/m3	-	-
----	-----------	-----------	---	---

## ETHYLBENZENE

UK	441 mg/m3	552 mg/m3	-	-
----	-----------	-----------	---	---

## O-XYLENE

EU	221 mg/m3	442 mg/m3	-	-
----	-----------	-----------	---	---

### DNEL/PNEC Values

**DNEL / PNEC** No data available.

### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Protective gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Liquid

**Colour:** Colourless

**Odour:** Characteristic odour

**Viscosity:** Non-viscous

**Flash point°C:** <23

### 9.2. Other information

**Other information:** No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions. Stable at room temperature.

### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

[cont...]

# SAFETY DATA SHEET

CELLULOSE THINNER

Page: 7

## 10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

## 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

## 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

Hazardous ingredients:

#### ACETONE

IVN	RAT	LD50	5500	mg/kg
ORL	MUS	LD50	3000	mg/kg
ORL	RAT	LD50	5800	mg/kg

#### TOLUENE

IVN	RAT	LD50	1960	mg/kg
ORL	MUS	LD50	2	gm/kg
ORL	RAT	LD50	6900	mg/kg

#### N-BUTYL ACETATE

ORL	MUS	LD50	6	gm/kg
ORL	RAT	LD50	10768	mg/kg

#### ETHANOL

IVN	RAT	LD50	1440	mg/kg
ORL	MUS	LD50	3450	mg/kg
ORL	RAT	LD50	7060	mg/kg

#### BUTAN-1-OL

IVN	RAT	LD50	310	mg/kg
ORL	MUS	LD50	2680	mg/kg
ORL	RAT	LD50	790	mg/kg

#### ISOBUTANOL

IVN	MUS	LD50	417	mg/kg
-----	-----	------	-----	-------

[cont...]

## SAFETY DATA SHEET

### CELLULOSE THINNER

Page: 8

IVN	RAT	LD50	340	mg/kg
ORL	RAT	LD50	2460	mg/kg

#### 4-METHYLPENTAN-2-ONE

IPR	RAT	LD50	400	mg/kg
ORL	MUS	LD50	1900	mg/kg
ORL	RAT	LD50	2080	mg/kg

#### M-XYLENE

IPR	MUS	LD50	2003	µl/kg
ORL	RAT	LD50	5	gm/kg

#### P-XYLENE

IPR	MUS	LD50	2450	µl/kg
IPR	RAT	LD50	3810	mg/kg
ORL	RAT	LD50	5	gm/kg

#### ETHYLBENZENE

IPR	MUS	LD50	2624	µl/kg
ORL	RAT	LD50	3500	mg/kg

#### O-XYLENE

IPR	MUS	LD50	1550	µl/kg
ORL	RAT	LDLO	5	gm/kg

#### Relevant hazards for substance:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Reproductive toxicity	--	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated
STOT-repeated exposure	-	Hazardous: calculated

#### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

[cont...]



# SAFETY DATA SHEET

CELLULOSE THINNER

Page: 9

## Section 12: Ecological information

### 12.1. Toxicity

**Hazardous ingredients:**

**ACETONE**

BLUEGILL (Lepomis macrochirus)
--------------------------------

LC50
------

8300	mg/l
------	------

### 12.2. Persistence and degradability

**Persistence and degradability:** Biodegradable.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No bioaccumulation potential.

### 12.4. Mobility in soil

**Mobility:** Readily absorbed into soil.

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

**Other adverse effects:** Negligible ecotoxicity.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

### 14.1. UN number

**UN number:** UN1993

### 14.2. UN proper shipping name

**Shipping name:** FLAMMABLE LIQUID, N.O.S.

### 14.3. Transport hazard class(es)

**Transport class:** 3

### 14.4. Packing group

**Packing group:** II

### 14.5. Environmental hazards

**Environmentally hazardous:** No

**Marine pollutant:** No

[cont...]

# SAFETY DATA SHEET

CELLULOSE THINNER

Page: 10

## 14.6. Special precautions for user

**Special precautions:** No special precautions.

**Tunnel code:** D/E

**Transport category:** 2

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Specific regulations:** Not applicable.

### 15.2. Chemical Safety Assessment

## Section 16: Other information

### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** EUH066: Repeated exposure may cause skin dryness or cracking.

H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H302: Harmful if swallowed.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H361d: Suspected of damaging the unborn child.

H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.