



## Safety Data Sheet S91 DARK ALUMINIUM

Safety Data Sheet dated 29/11/1997 version 6.1 dated 18/12/2015

This safety data sheet has been completely updated in compliance to Regulation 2015/830/EU.

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Mixture identification:

Trade name:

INDURA - UNIVERSAL DARK ALUMINIUM COLOURANT

Trade code:

S91

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against Recommended use:

#### 1.3. Details of the supplier of the safety data sheet

Seller: Capella Solutions Group. Second Avenue, Chatham, Kent ME4 5AU

Tel. +44 (0)1634 823907 - Fax +44 (0)1634 823909

Competent person responsible for the safety data sheet: salescapellasolutionsgroup.com

#### 1.4. Emergency telephone number Tel: +44(0) 1634 823900 (08.00 / 17.00)

UK: NPIS National Poisons Information Centre Tel: +44 0344 892 0111

IRL: Beaumont Hospital - National Poisons Information Centre: Tel: +353 1 8092566

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP):

- ⚠ Warning, Flam. Liq. 3, Flammable liquid and vapour.
- ⚠ Warning, Acute Tox. 4, Harmful if inhaled.
- ⚠ Warning, Skin Irrit. 2, Causes skin irritation.
- ⚠ Warning, Eye Irrit. 2, Causes serious eye irritation.
- ⚠ Warning, STOT SE 3, May cause respiratory irritation.
- ⚠ Warning, STOT RE 2, May cause damage to organs through prolonged or repeated exposure.

Adverse physicochemical, human health and environmental effects:

No other hazards

#### 2.2. Label elements

Symbols:



Warning

Hazard statements:

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280 Wear protective gloves/clothing and eye/face protection.

P312 Call a POISON CENTER/ doctor/if you feel unwell.

# Safety Data Sheet

## S91 DARK ALUMINIUM

P314 Get medical advice/attention if you feel unwell.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire, use a foam fire extinguisher to extinguish.

Special Provisions:

None

Contents:

Xylene [Reaction mass of ethylbenzene and m-xylene and p-xylene] (Benzene < 0,01%)  
xylene

Hydrocarbons, C9, aromatics

2-butanone oxime; ethyl methyl ketoxime: May produce an allergic reaction.

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards:

No other hazards

---

### SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

>= 30% - < 40% Xylene [Reaction mass of ethylbenzene and m-xylene and p-xylene] (Benzene < 0,01%)

REACH No.: 01-2119555267-33, EC: 905-562-9

⚠ 2.6/3 Flam. Liq. 3 H226

⚠ 3.10/1 Asp. Tox. 1 H304

⚠ 3.3/2 Eye Irrit. 2 H319

⚠ 3.8/3 STOT SE 3 H335

⚠ 3.9/2 STOT RE 2 H373

⚠ 3.2/2 Skin Irrit. 2 H315

⚠ 3.1/4/Dermal Acute Tox. 4 H312

⚠ 3.1/4/Inhal Acute Tox. 4 H332

>= 15% - < 20% xylene

REACH No.: 01-2119488216-32, Index number: 601-022-00-9, CAS: 1330-20-7, EC: 215-535-7

⚠ 2.6/3 Flam. Liq. 3 H226

⚠ 3.10/1 Asp. Tox. 1 H304

⚠ 3.3/2 Eye Irrit. 2 H319

⚠ 3.8/3 STOT SE 3 H335

⚠ 3.9/2 STOT RE 2 H373

⚠ 3.2/2 Skin Irrit. 2 H315

⚠ 3.1/4/Dermal Acute Tox. 4 H312

⚠ 3.1/4/Inhal Acute Tox. 4 H332

>= 7% - < 10% aluminium powder (stabilised)

REACH No.: 01-2119529243-45, Index number: 013-002-00-1, CAS: 7429-90-5, EC: 231-072-3

⚠ 2.12/2 Water-react. 2 H261

⚠ 2.7/1 Flam. Sol. 1 H228

>= 3% - < 5% Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

REACH No.: 01-2119463258-33, EC: 919-857-5

⚠ 2.6/3 Flam. Liq. 3 H226

⚠ 3.10/1 Asp. Tox. 1 H304

⚠ 3.8/3 STOT SE 3 H336

EUH066

# Safety Data Sheet

## S91 DARK ALUMINIUM

>= 1% - < 3% Hydrocarbons, C9, aromatics

REACH No.: 01-2119455851-35, EC: 918-668-5

⚠ 2.6/3 Flam. Liq. 3 H226

⚠ 3.8/3 STOT SE 3 H335

⚠ 3.10/1 Asp. Tox. 1 H304

⚠ 3.8/3 STOT SE 3 H336

⚠ 4.1/C2 Aquatic Chronic 2 H411

EUH066

>= 1% - < 3% n-butyl acetate

REACH No.: 01-2119485493-29, Index number: 607-025-00-1, CAS: 123-86-4, EC: 204-658-1

⚠ 2.6/3 Flam. Liq. 3 H226

⚠ 3.8/3 STOT SE 3 H336

EUH066

>= 0.5% - < 1% 2-butanone oxime; ethyl methyl ketoxime

REACH No.: 01-2119539477-28, Index number: 616-014-00-0, CAS: 96-29-7, EC: 202-496-6

⚠ 3.6/2 Carc. 2 H351

⚠ 3.3/1 Eye Dam. 1 H318

⚠ 3.4.2/1-1A-1B Skin Sens. 1,1A,1B H317

⚠ 3.1/4/Dermal Acute Tox. 4 H312

>= 0.25% - < 0.5% ethylbenzene

REACH No.: 01-2119489370-35, Index number: 601-023-00-4, CAS: 100-41-4, EC: 202-849-4

⚠ 2.6/2 Flam. Liq. 2 H225

⚠ 3.1/4/Inhal Acute Tox. 4 H332

⚠ 3.9/2 STOT RE 2 H373

⚠ 3.10/1 Asp. Tox. 1 H304

The full text of H-phrases is shown in section 16.

---

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do NOT induce vomiting.

In case of Inhalation:

If breathing is irregular or stopped, administer artificial respiration.

In case of inhalation, consult a doctor immediately and show him packing or label.

#### 4.2. Most important symptoms and effects, both acute and delayed

None

#### 4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

# Safety Data Sheet

## S91 DARK ALUMINIUM

None

---

### SECTION 5: Firefighting measures

- 5.1. Extinguishing media
  - Suitable extinguishing media:
  - Extinguishing media which must not be used for safety reasons:
  - None in particular.
- 5.2. Special hazards arising from the substance or mixture
  - Do not inhale explosion and combustion gases.
  - Burning produces heavy smoke.
- 5.3. Advice for firefighters
  - Use suitable breathing apparatus .
  - Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
  - Move undamaged containers from immediate hazard area if it can be done safely.

---

### SECTION 6: Accidental release measures

- 6.1. Personal precautions, protective equipment and emergency procedures
  - Wear personal protection equipment.
  - Remove all sources of ignition.
  - Wear breathing apparatus if exposed to vapours/dusts/aerosols.
  - Provide adequate ventilation.
  - Use appropriate respiratory protection.
  - See protective measures under point 7 and 8.
- 6.2. Environmental precautions
  - Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
  - Retain contaminated washing water and dispose it.
  - In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.
  - Suitable material for taking up: absorbing material, organic, sand
- 6.3. Methods and material for containment and cleaning up
  - Wash with plenty of water.
- 6.4. Reference to other sections
  - See also section 8 and 13

---

### SECTION 7: Handling and storage

- 7.1. Precautions for safe handling
  - Avoid contact with skin and eyes, inhalation of vapours and mists.
  - Use localized ventilation system.
  - Don't use empty container before they have been cleaned.
  - Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
  - Contaminated clothing should be changed before entering eating areas.
  - Do not eat or drink while working.
  - See also section 8 for recommended protective equipment.
- 7.2. Conditions for safe storage, including any incompatibilities
  - Store at below 20 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.
  - Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.
  - Keep away from food, drink and feed.
  - Incompatible materials:
  - None in particular.
  - Instructions as regards storage premises:
  - Cool and adequately ventilated.
- 7.3. Specific end use(s)
  - None in particular

# Safety Data Sheet

## S91 DARK ALUMINIUM

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Xylene [Reaction mass of ethylbenzene and m-xylene and p-xylene] (Benzene < 0,01%)  
EU - LTE(8h): 221 mg/m<sup>3</sup>, 50 ppm - STE: 442 mg/m<sup>3</sup>, 100 ppm - Notes: Bold-type:  
Indicative Occupational Exposure Limit Values [2,3] and Limit Values for Occupational  
Exposure [4] (for references see bibliography)  
ACGIH - LTE(8h): 100 ppm - STE: 150 ppm - Notes: A4, BEI - URT and eye irr, CNS  
impair

xylene - CAS: 1330-20-7  
EU - LTE(8h): 221 mg/m<sup>3</sup>, 50 ppm - STE: 442 mg/m<sup>3</sup>, 100 ppm - Notes: Bold-type:  
Indicative Occupational Exposure Limit Values [2,3] and Limit Values for Occupational  
Exposure [4] (for references see bibliography)  
ACGIH - LTE(8h): 100 ppm - STE: 150 ppm - Notes: A4, BEI - URT and eye irr, CNS  
impair

aluminium powder (stabilised) - CAS: 7429-90-5  
ACGIH - LTE(8h): 1 mg/m<sup>3</sup>, 0.9 ppm - Notes: Frazione Respirabile

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics  
ACGIH - LTE(8h): 1200 mg/m<sup>3</sup>, 197 ppm

Hydrocarbons, C9, aromatics  
ACGIH - LTE(8h): 100 mg/m<sup>3</sup>, 19 ppm

n-butyl acetate - CAS: 123-86-4  
ACGIH - LTE(8h): 713 mg/m<sup>3</sup>, 150 ppm - STE: 950 mg/m<sup>3</sup>, 200 ppm - Notes: Eye and  
URT irr

ethylbenzene - CAS: 100-41-4  
EU - LTE(8h): 442 mg/m<sup>3</sup>, 100 ppm - STE: 884 mg/m<sup>3</sup>, 200 ppm - Notes: Bold-type:  
Indicative Occupational Exposure Limit Values [2,3] and Limit Values for Occupational  
Exposure [4] (for references see bibliography)  
ACGIH - LTE(8h): 20 ppm - Notes: A3, BEI - URT irr, kidney dam (nephropathy),  
cochlear impair

#### DNEL Exposure Limit Values

Xylene [Reaction mass of ethylbenzene and m-xylene and p-xylene] (Benzene < 0,01%)  
Consumer: 260 ppm - Exposure: Human Inhalation - Frequency: Short Term (acute)  
Consumer: 65.3 ppm - Exposure: Human Inhalation - Frequency: Long Term (repeated)

xylene - CAS: 1330-20-7  
Worker Industry: 289 mg/m<sup>3</sup> - Worker Professional: 289 mg/m<sup>3</sup> - Consumer: 174 mg/m<sup>3</sup>  
- Exposure: Human Inhalation - Frequency: Short Term, local effects  
Worker Industry: 77 mg/m<sup>3</sup> - Worker Professional: 77 mg/m<sup>3</sup> - Consumer: 14.8 mg/m<sup>3</sup> -  
Exposure: Human Inhalation - Frequency: Long Term, systemic effects  
Worker Industry: 180 mg/kg/d - Worker Professional: 180 mg/kg/d - Consumer: 108  
mg/kg/d - Exposure: Human Dermal - Frequency: Long Term, systemic effects  
Consumer: 1.6 mg/kg/d - Exposure: Human Oral  
Frequency: Long Term, systemic effects

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics  
Worker Industry: 208 mg/kg - Worker Professional: 208 mg/kg - Consumer: 125 mg/kg -  
Exposure: Human Dermal - Frequency: Long Term, systemic effects  
Worker Industry: 871 mg/m<sup>3</sup> - Worker Professional: 871 mg/m<sup>3</sup> - Consumer: 185 mg/m<sup>3</sup>  
- Exposure: Human Inhalation - Frequency: Long Term, systemic effects  
Consumer: 125 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

Hydrocarbons, C9, aromatics  
Consumer: 11 mg/kg/d - Exposure: Human Oral - Frequency: Long Term, systemic  
effects  
Worker Industry: 150 mg/m<sup>3</sup> - Worker Professional: 150 mg/m<sup>3</sup> - Consumer: 32 mg/m<sup>3</sup> -  
Exposure: Human Inhalation - Frequency: Long Term, systemic effects  
Worker Industry: 25 mg/kg/d - Worker Professional: 25 mg/kg/d - Consumer: 11 mg/kg/d  
- Exposure: Human Dermal - Frequency: Long Term, systemic effects

n-butyl acetate - CAS: 123-86-4

## Safety Data Sheet

### S91 DARK ALUMINIUM

Worker Industry: 960 mg/m<sup>3</sup> - Worker Professional: 960 mg/m<sup>3</sup> - Consumer: 859.7 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, local effects  
Worker Industry: 480 mg/m<sup>3</sup> - Worker Professional: 480 mg/m<sup>3</sup> - Consumer: 102.34 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, local effects  
Worker Industry: 7 mg/kg/d - Worker Professional: 7 mg/kg/d - Consumer: 3.4 mg/kg/d - Exposure: Human Dermal - Frequency: Long Term, systemic effects  
Consumer: 3.4 mg/kg/d - Exposure: Human Oral - Frequency: Long Term, systemic effects

2-butanone oxime; ethyl methyl ketoxime - CAS: 96-29-7

Worker Professional: 2.5 mg/kg - Consumer: 1.5 mg/kg - Exposure: Human Dermal - Frequency: Short Term, systemic effects

Worker Professional: 1.3 mg/kg - Consumer: 0.78 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Professional: 9 ppm - Consumer: 2.7 ppm - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Professional: 3.33 ppm - Consumer: 2 ppm - Exposure: Human Inhalation - Frequency: Long Term, local effects

#### PNEC Exposure Limit Values

Xylene [Reaction mass of ethylbenzene and m-xylene and p-xylene] (Benzene < 0,01%)

Target: Fresh Water - Value: 0.327 mg/l

Target: Marine water - Value: 0.327 mg/l

Target: Freshwater sediments - Value: 12.46 mg/kg

Target: Marine water - Value: 12.46 mg/kg

Target: Soil (agricultural) - Value: 2.31 mg/kg

xylene - CAS: 1330-20-7

Target: Fresh Water - Value: 0.327 mg/l

Target: Marine water - Value: 0.327 mg/l

Target: Freshwater sediments - Value: 12.46 mg/kg

Target: Marine water - Value: 12.46 mg/kg

Target: Soil (agricultural) - Value: 2.31 mg/kg

n-butyl acetate - CAS: 123-86-4

Target: Soil (agricultural) - Value: 0.0903 mg/kg

Target: Fresh Water - Value: 0.18 mg/l

Target: Marine water - Value: 0.018 mg/l

Target: Freshwater sediments - Value: 0.981 mg/kg

Target: Marine water sediments - Value: 0.0981 mg/kg

2-butanone oxime; ethyl methyl ketoxime - CAS: 96-29-7

Target: Fresh Water - Value: 0.256 mg/l

Target: Microorganisms in sewage treatments - Value: 177 mg/l

#### 8.2. Exposure controls

##### Eye protection:

Use close fitting safety goggles, don't use eye lens.

##### Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

##### Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

##### Respiratory protection:

Use respiratory protection where ventilation is insufficient or exposure is prolonged.

Use adequate protective respiratory equipment.

##### Thermal Hazards:

None

##### Environmental exposure controls:

None

##### Appropriate engineering controls:

None

# Safety Data Sheet

## S91 DARK ALUMINIUM

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes:
Appearance and colour:	liquid aluminium	--	--
Odour:	Characteristic	--	--
Odour threshold:	N.A.	--	--
pH:	N.A.	--	--
Melting point / freezing point:	N.A.	--	--
Initial boiling point and boiling range:	137°C	--	--
Flash point:	25 °C	--	--
Evaporation rate:	N.A.	--	--
Solid/gas flammability:	N.A.	--	--
Upper/lower flammability or explosive limits:	N.A.	--	--
Vapour pressure:	N.A.	--	--
Vapour density:	> 1	--	--
Relative density:	1.000 g/cm <sup>3</sup> - 20°C	--	--
Solubility in water:	insoluble	--	--
Solubility in oil:	N.A.	--	--
Partition coefficient (n-octanol/water):	N.A.	--	--
Auto-ignition temperature:	> 400°C	--	--
Decomposition temperature:	N.A.	--	--
Viscosity:	N.A.	--	--
Explosive properties:	N.A.	--	--
Oxidizing properties:	N.A.	--	--

#### 9.2. Other information

# Safety Data Sheet

## S91 DARK ALUMINIUM

Properties	Value	Method:	Notes:
Miscibility:	N.A.	--	--
Fat Solubility:	N.A.	--	--
Conductivity:	N.A.	--	--
Substance Groups relevant properties	N.A.	--	--

---

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Stable under normal conditions

#### 10.2. Chemical stability

Stable under normal conditions

#### 10.3. Possibility of hazardous reactions

None

#### 10.4. Conditions to avoid

Stable under normal conditions.

#### 10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

#### 10.6. Hazardous decomposition products

None.

---

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Toxicological information of the mixture:

N.A.

Toxicological information of the main substances found in the mixture:

xylene - CAS: 1330-20-7

a) acute toxicity:

Test: LC50 - Route: Inhalation Vapour - Species: Rat > 20 mg/l - Duration: 4h

Test: LD50 - Route: Skin - Species: Rabbit > 4200 mg/kg

Test: LD50 - Route: Oral - Species: Rat = 3500 mg/kg

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat > 4951 mg/m3 - Duration: 4h

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg

Hydrocarbons, C9, aromatics

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat > 6193 mg/m3 - Duration: 4h

Test: LD50 - Route: Oral - Species: Rat = 3592 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 3160 mg/kg

n-butyl acetate - CAS: 123-86-4

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat > 21.1 mg/l - Duration: 4h

Test: LD50 - Route: Oral - Species: Rat = 10760 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 14000 mg/kg

2-butanone oxime; ethyl methyl ketoxime - CAS: 96-29-7

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 2400 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 1000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat = 20 mg/l - Duration: 4h



# Safety Data Sheet

## S91 DARK ALUMINIUM

If not differently specified, the information required in Regulation (EU)2015/830 listed below must be considered as N.A.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard.

---

### SECTION 12: Ecological information

#### 12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

xylene - CAS: 1330-20-7

##### a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 1 ml/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia = 1 mg/l - Duration h: 24

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

##### a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae > 1000 mg/l - Duration h: 72

Endpoint: EC50 - Species: Daphnia > 1000 mg/l - Duration h: 48

Endpoint: LC50 - Species: Fish > 1000 mg/l - Duration h: 96

##### b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia = 100 mg/l - Notes: 21 gg

Endpoint: NOEC - Species: Fish = 0.131 mg/l - Notes: 28 gg

n-butyl acetate - CAS: 123-86-4

##### a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 18 mg/l - Duration h: 96

Endpoint: EC50 - Species: Algae = 648 mg/l - Duration h: 72

Endpoint: EC50 - Species: Daphnia = 44 mg/l - Duration h: 48

2-butanone oxime; ethyl methyl ketoxime - CAS: 96-29-7

##### a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 201 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 11.8 mg/l - Duration h: 72

Endpoint: LC50 - Species: Fish > 100 mg/l - Duration h: 96

Endpoint: NOEC - Species: Algae = 2.56 mg/l - Duration h: 72

#### 12.2. Persistence and degradability

None

n-butyl acetate - CAS: 123-86-4

Biodegradability: Readily biodegradable - Test: N.A. - Duration: N.A. - %: N.A. - Notes: N.A.

#### 12.3. Bioaccumulative potential

N.A.

#### 12.4. Mobility in soil

N.A.

#### 12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

#### 12.6. Other adverse effects

None

---

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

# Safety Data Sheet

## S91 DARK ALUMINIUM

---

### SECTION 14: Transport information



- 14.1. UN number  
ADR-UN Number: 1263  
IATA-UN Number: 1263  
IMDG-UN Number: 1263
- 14.2. UN proper shipping name  
ADR-Shipping Name: PAINT  
IATA-Shipping Name: PAINT  
IMDG-Shipping Name: PAINT
- 14.3. Transport hazard class(es)  
ADR-Class: 3  
  
ADR - Hazard identification number: 30  
IATA-Class: 3  
IATA-Label: 3  
IMDG-Class: 3  
Sea (IMO): Classe 3, P.G. III - EmS F-E, S-E
- 14.4. Packing group  
ADR-Packing Group: III  
IATA-Packing group: III  
IMDG-Packing group: III
- 14.5. Environmental hazards  
ADR-Environmental Pollutant: No  
IMDG-Marine pollutant: No
- 14.6. Special precautions for user  
  
ADR-Subsidiary risks: -  
ADR-S.P.: 163 640E 650  
ADR-Tunnel Restriction Code: (D/E)  
IATA-Passenger Aircraft: 355  
IATA-Subsidiary risks: -  
IATA-Cargo Aircraft: 366  
IATA-S.P.: A3 A72  
IATA-ERG: 3L  
  
IMDG-EmS: F-E , S-E  
IMDG-Subsidiary risks: -  
  
IMDG-Storage category: Category A  
IMDG-Storage notes: -
- 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code  
No

---

### SECTION 15: Regulatory information

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture  
Dir. 98/24/EC (Risks related to chemical agents at work)  
Dir. 2000/39/EC (Occupational exposure limit values)  
Regulation (EC) n. 1907/2006 (REACH)  
Regulation (EC) n. 1272/2008 (CLP)  
Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

# Safety Data Sheet

## S91 DARK ALUMINIUM

Regulation (EU) 2015/830  
Regulation (EU) n. 286/2011 (ATP 2 CLP)  
Regulation (EU) n. 618/2012 (ATP 3 CLP)  
Regulation (EU) n. 487/2013 (ATP 4 CLP)  
Regulation (EU) n. 944/2013 (ATP 5 CLP)  
Regulation (EU) n. 605/2014 (ATP 6 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3

Restriction 40

Restrictions related to the substances contained:

No restriction.

Volatile Organic compounds - VOCs = 55.53 %

Volatile Organic compounds - VOCs = 560.36 g/l

Volatile CMR substances = 0.00 %

Halogenated VOCs which are assigned the risk phrase R40 = 0.90 %

Organic Carbon - C = 0.49

Where applicable, refer to the following regulatory provisions :

Directive 82/501/EEC ('Activities linked to risks of serious accidents') and subsequent amendments.

Regulation (EC) nr 648/2004 (detergents).

1999/13/EC (VOC directive)

Provisions related to directives 82/501/EC(Seveso), 96/82/EC(Seveso II):

N.A.

15.2. Chemical safety assessment

No

---

### SECTION 16: Other information

Text of phrases referred to under heading 3:

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H315 Causes skin irritation.

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H261 In contact with water releases flammable gases.

H228 Flammable solid.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

H411 Toxic to aquatic life with long lasting effects.

H351 Suspected of causing cancer.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H225 Highly flammable liquid and vapour.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

CCNL - Appendix 1

Insert further consulted bibliography

The information contained herein is based on our state of knowledge at the above-specified date. It

# Safety Data Sheet

## S91 DARK ALUMINIUM

refers solely to the product indicated and constitutes no guarantee of particular quality.  
It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
WGK:	German Water Hazard Class.
N.A.:	N.A.
N.D.:	