



# **PRIMERS**

Size 500ml

Code: GP500 - REDP500 - WP500 - YP500

#### **Products Characteristics**

- Excellent corrosion prevention
- · Optimizes the gloss finish of the topcoat
- · Fast drying with good spraying properties andgood coverage
- · Excellent adhesion of subsequent topcoat
- · Excellent filling properties and easy to sand
- Will adhere to wood, metal, aluminium and many other substrates.

# Physical and chemical data

Product Type	Nitro Combi
Coverage	1.56 - 2.19m² per 500ml
Drying times	Dust Free 5 - 10minutes Touch Dry 10 - 20 minutes Sand able 15 minutes Overcoat able 15 –30 minutes
The drying time depends on temperature, humidity and the thickness of the applied coat.	

# **Surface Preparation**

- · De-rust, abrade and clean surfaces prior to coating
- The surface must be free from all contamination including rust, grease and moisture.
- Before use, carefully read and note the warning text on the label

### **Environmentally sound**

The products supplied by ProXL are 100% free of heavy metals and the caps and packaging are made of recyclable material.

## **Disposal**

Completely emptied cans should be put in recycling skips or appropriate container. Cans which are not empty should be disposed off as special refuse.

This application and technical information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively is the responsibility of the user.

