



ZINC RICH

Size 500m

Codes: ZR500

Products Characteristics

- High quality zinc coating with more than 90% zinc share in the dry film
- Cathodic corrosion protection for all bare metals providing resistance to the highest demands against corrosion.
- Resistant to heats of up to 350°c
- Fast drying
- · Highly suitable for welding seams
- · Resistant to petrol, chemicals and weather influences

Physical and chemical data

Product Type	Epoxyester
Coverage	1.56 - 2.19m² per 500ml
Drying times	Dust Free 10 - 15 minutes Touch Dry 20 - 30 minutes Overcoatable after 24 hours Resistant to heat after 8 - 12 hours
The drying time depends on temperature, humidity and the thickness of the applied coat.	

Surface Preparation

- The surface must be free from all contamination including rust, grease and moisture.
- Before application, ensure that the mixing balls in the aerosol are moving freely as this ensures that the zinc content is being physically mixed into the paint.

Environmentally sound

The products supplied by ProXL are 100% free of heavy metals and the caps and packaging are made of recyclable material.

Disposal

Completely emptied cans should be put in recycling skips or appropriate container. Cans which are not empty should be disposed off as special refuse.

This application and technical information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively is the responsibility of the user.

