

AUTOMOTIVE BONDING PRODUCTS



adhesives / sealants / foams

Automotive Product Range

Article Number	Polymix automotive products	Cartridges sizes	Product color	Working time*	Sanding time*	Painting time	Application
PLASTIC REPAIR ADHESIVES							
PROPLAS-R	ProPLAS Ultra Fast Adhesive	50ml	Black	35 seconds	15 minutes	40 minutes	Two part urethane adhesive with a ultra fast gel and curing time. Can be use used for general purpose gluing or to hold part in position.
PROPLAS-F	ProPLAS Plastic Repair & Adhesive	50ml	Black	1 minute	20 minutes	1 hour	Two part urethane plastic repair structural adhesive to repair any kind of plastic part. One minute working time makes this product suitable for small size repairs.
PROPLAS-FC	ProPLAS Plastic Repair & Adhesive	50ml	Clear	1 minute	20 minutes	1 hour	Two part urethane plastic repair structural adhesive to repair any kind of plastic part. One minute working time makes this product suitable for small size repairs.
PROPLAS-S	ProPLAS Plastic Repair & Adhesive	50ml	Black	5 minutes	30 minutes	90 minutes	Two part urethane plastic repair structural adhesive to repair any kind of plastic part. Five minutes working time makes this product suitable for large size repairs.

SEAM SEALERS							
PROSEAL-SL	ProSEAL Self Leveling Seam Sealer	50ml	Grey Ochre	15 minutes	-	30 minutes	Self-Leveling Seam Sealer is a two component urethane seam sealer used to match the OEM seams for trunk seams, drip rails, roof seams and core supports.
PROSEAL-SL200		200ml					
PROSEAL-MB	ProSEAL Low/Medium Build Seam Sealer	50ml	Grey Ochre	15 minutes	-	30 minutes	Two part urethane non-sag seam sealer duplicates a factory appearance on truck bed seams, tooled door skin seams, floor pan seams, core support seams. To be used to re-create the sprayed effect.
PROSEAL-MB200		200ml					
PROSEAL-HB	ProSEAL High Build Seam Sealer	50ml	Grey Ochre	15 minutes	-	30 minutes	Two part urethane for use in vertical or horizontal seams to match OEM sealers applied in rectangular shaped beed. Non-sagging, non-flowing. To be used to re-create the sprayed and brushed effect.
PROSEAL-HB200		200ml					

METAL PANEL BONDING							
PROMET	ProMET 2K PU Metal Repair	50ml	Black	1 hour	8 hours	12 hours	Two part urethane used to bond steel and aluminum . The primary use is to replace quarter panels, roofs, box sides, van sides, utility vehicle sides and door skins.

FOAMS							
PROFOAM-W	ProFOAM Fast Rigid Foam	50ml	White	1 minute	-	1 hour	Two part urethane which foams in place to fill posts, pillars, and automotive body cavities. White color hard density.
PROFOAM-W200	- White	200ml					
PROFOAM-G	ProFOAM Fast Semi - Rigid Foam	50ml	Grey	1 minute	-	1 hour	Two part urethane which foams in place to fill posts, pillars, and automotive body cavities. Grey color soft density.
PROFOAM-G200	- Grey	200ml					

* Working time and sanding time are referred to a room temperature of 20°C, performances may change due to temperature variation