



SAFETY DATA SHEET

PROMIX ECLIPSE - HS SCRATCH RESISTANT LACQUER

Page: 1

Compilation date: 23/10/2012

Revision date: 02/01/2018

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: PROMIX ECLIPSE - HS SCRATCH RESISTANT LACQUER

Product code: EHSC

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: ProMIX Eclipse
Second Avenue
Luton
Chatham
Kent
ME4 5AU
United Kingdom

Tel: 01634 823900

Fax: 01634 813807

Email: sales@capellasolutionsgroup.com

1.4. Emergency telephone number

Emergency tel: +44(0) 1634 823900 (08.00 / 17.00)

UK: NPIS National Poisons Information Centre Tel: +44 0344 892 0111

IRL: Beaumont Hospital - National Poisons Information Centre: Tel: +353 1 8092566

(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Aquatic Chronic 3: H412; Flam. Liq. 3: H226; STOT SE 3: H336

Most important adverse effects: Flammable liquid and vapour. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: H226: Flammable liquid and vapour.

H336: May cause drowsiness or dizziness.

H412: Harmful to aquatic life with long lasting effects.

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark

[cont...]

SAFETY DATA SHEET

PROMIX ECLIPSE - HS SCRATCH RESISTANT LACQUER

Page: 2



Signal words: Warning

Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241: Use explosion-proof electrical/ventilating/lighting/.. equipment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+352: IF ON SKIN: Wash with plenty of water/.

P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

N-BUTYL ACETATE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
204-658-1	123-86-4	-	Flam. Liq. 3: H226; STOT SE 3: H336; -: EUH066	30-50%

LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.

265-199-0	64742-95-6	-	Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H335; Aquatic Chronic 2: H411	1-10%
-----------	------------	---	---	-------

2-METHOXY-1-METHYLETHYL ACETATE

203-603-9	108-65-6	Substance with a Community workplace exposure limit.	Flam. Liq. 3: H226	1-10%
-----------	----------	---	--------------------	-------

M-XYLENE

203-576-3	108-38-3	-	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315	1-10%
-----------	----------	---	--	-------

P-XYLENE

203-396-5	106-42-3	-	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315	1-10%
-----------	----------	---	--	-------

[cont...]

SAFETY DATA SHEET

PROMIX ECLIPSE - HS SCRATCH RESISTANT LACQUER

Page: 3

ETHYLBENZENE

202-849-4	100-41-4	-	Flam. Liq. 2: H225; Acute Tox. 4: H332; STOT RE 2: H373; Asp. Tox. 1: H304	1-10%
-----------	----------	---	---	-------

O-XYLENE

202-422-2	95-47-6	-	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315	1-10%
-----------	---------	---	--	-------

BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE (A)

255-437-1	41556-26-7	-	Skin Sens. 1: H317; Aquatic Acute 1: H400; Aquatic Chronic 4: H413; Resp. Sens. 1: H334	<1%
-----------	------------	---	---	-----

METHYL METHACRYLATE

201-297-1	80-62-6	-	Flam. Liq. 2: H225; STOT SE 3: H335; Skin Irrit. 2: H315; Skin Sens. 1: H317	<1%
-----------	---------	---	---	-----

2-HYDROXYETHYL METHACRYLATE

212-782-2	868-77-9	-	Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317	<1%
-----------	----------	---	--	-----

GLYCIDYL NEODECANOATE

247-979-2	26761-45-5	-	-	<1%
-----------	------------	---	---	-----

3-(3-(2H-BENZOTRIAZOL-2-YL)-5-T-BUTYL-4-HYDROXYPHENYL) PROPIONOL-OHYDROXYPOLY(OXYETHYLENE)

-	4008-30-7	-	-	<1%
---	-----------	---	---	-----

SEBACATO DI METILE E 1,2,2,6,6-PENTAMETIL-4-PIPERIDILE (A)

280-060-4	82919-37-7	-	-	<1%
-----------	------------	---	---	-----

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

Inhalation: Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

[cont...]

SAFETY DATA SHEET

PROMIX ECLIPSE - HS SCRATCH RESISTANT LACQUER

Page: 4

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Notify the police and fire brigade immediately. Eliminate all sources of ignition. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Smoking is forbidden. Use non-sparking tools. Ensure there is sufficient ventilation of the area. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

7.3. Specific end use(s)

Specific end use(s): No data available.

[cont...]

SAFETY DATA SHEET

PROMIX ECLIPSE - HS SCRATCH RESISTANT LACQUER

Page: 5

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

N-BUTYL ACETATE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	724 mg/m ³	966 mg/m ³	-	-

2-METHOXY-1-METHYLETHYL ACETATE

UK	274 mg/m ³	548 mg/m ³	-	-
----	-----------------------	-----------------------	---	---

M-XYLENE

EU	221 mg/m ³	442 mg/m ³	-	-
----	-----------------------	-----------------------	---	---

P-XYLENE

EU	221 mg/m ³	442 mg/m ³	-	-
----	-----------------------	-----------------------	---	---

ETHYLBENZENE

UK	441 mg/m ³	552 mg/m ³	-	-
----	-----------------------	-----------------------	---	---

O-XYLENE

EU	221 mg/m ³	442 mg/m ³	-	-
----	-----------------------	-----------------------	---	---

METHYL METHACRYLATE

UK	50 ppm	100 ppm	-	-
----	--------	---------	---	---

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Characteristic odour

Boiling point/range°C: 124

Flammability limits %: lower: 1.2

upper: 7.5

[cont...]

SAFETY DATA SHEET

PROMIX ECLIPSE - HS SCRATCH RESISTANT LACQUER

Page: 6

Autoflammability°C: 315

Relative density: 0.985

Flash point°C: 25

Vapour pressure: 10.7 hPa

VOC g/l: 453.2

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

N-BUTYL ACETATE

ORL	MUS	LD50	6	gm/kg
ORL	RAT	LD50	10768	mg/kg

LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.

ORL	RAT	LD50	8400	mg/kg
-----	-----	------	------	-------

2-METHOXY-1-METHYLETHYL ACETATE

IPR	MUS	LD50	750	mg/kg
ORL	RAT	LD50	8532	mg/kg

[cont...]

SAFETY DATA SHEET

PROMIX ECLIPSE - HS SCRATCH RESISTANT LACQUER

Page: 7

M-XYLENE

IPR	MUS	LD50	2003	µl/kg
ORL	RAT	LD50	5	gm/kg

P-XYLENE

IPR	MUS	LD50	2450	µl/kg
IPR	RAT	LD50	3810	mg/kg
ORL	RAT	LD50	5	gm/kg

ETHYLBENZENE

IPR	MUS	LD50	2624	µl/kg
ORL	RAT	LD50	3500	mg/kg

O-XYLENE

IPR	MUS	LD50	1550	µl/kg
ORL	RAT	LDLO	5	gm/kg

METHYL METHACRYLATE

IPR	RAT	LD50	1328	mg/kg
ORL	MUS	LD50	3625	mg/kg
ORL	RAT	LD50	7872	mg/kg

2-HYDROXYETHYL METHACRYLATE

IPR	RAT	LD50	1250	mg/kg
ORL	MUS	LD50	3275	mg/kg
ORL	RAT	LD50	5050	mg/kg

Relevant hazards for substance:

Hazard	Route	Basis
STOT-single exposure	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

[cont...]

SAFETY DATA SHEET

PROMIX ECLIPSE - HS SCRATCH RESISTANT LACQUER

Page: 8

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1263

14.2. UN proper shipping name

Shipping name: PAINT

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 3

[cont...]

SAFETY DATA SHEET

PROMIX ECLIPSE - HS SCRATCH RESISTANT LACQUER

Page: 9

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H400: Very toxic to aquatic life.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

H413: May cause long lasting harmful effects to aquatic life.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

