

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 18.05.2016



Version number 1

Revision: 18.05.2016

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

- **1.1 Product identifier**
- **Trade name: ProXL® PLASTICOLOUR AEROSOL TRAFFIC BLACK 400 ML**
- **Article number: PC5TB**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use**  
 SU21 Consumer uses: Private households / general public / consumers  
 SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Product category PC9a** Coatings and paints, thinners, paint removers
- **Process category**  
 PROC7 Industrial spraying  
 PROC11 Non industrial spraying
- **Environmental release category**  
 ERC8a Wide dispersive indoor use of processing aids in open systems  
 ERC8d Wide dispersive outdoor use of processing aids in open systems
- **Application of the substance / the mixture** Spray varnish
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
 ProXL  
 Second Avenue  
 Chatham  
 Kent  
 ME4 5AU  
 Tel: +44 (0)1634 823900  
 Fax: +44 (0)1634 823909  
 Email: info@pro-xl.co.uk
- **Further information obtainable from:** Department Product Safety
- **1.4 Emergency telephone number:** Tel: +44(0) 1634 823900 (08.00 / 17.00)

**SECTION 2: Hazards identification**

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
- 
 GHS02 flame  
 Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
- 
 GHS07  
 Eye Irrit. 2 H319 Causes serious eye irritation.  
 STOT SE 3 H336 May cause drowsiness or dizziness.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
 The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 18.05.2016

Version number 1

Revision: 18.05.2016

Trade name: ProXL® PLASTICOLOUR AEROSOL TRAFFIC BLACK 400 ML

(Contd. of page 1)

## · Hazard pictograms



GHS02 GHS07

· Signal word *Danger*

## · Hazard-determining components of labelling:

acetone  
n-butyl acetate  
butan-1-ol  
propan-2-ol

## · Hazard statements

H222-H229 *Extremely flammable aerosol. Pressurised container: May burst if heated.*  
H319 *Causes serious eye irritation.*  
H336 *May cause drowsiness or dizziness.*

## · Precautionary statements

P102 *Keep out of reach of children.*  
P260 *Do not breathe spray.*  
P210 *Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.*  
P251 *Do not pierce or burn, even after use.*  
P211 *Do not spray on an open flame or other ignition source.*  
P410+P412 *Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.*  
P501 *Dispose of contents/container in accordance with local regulations.*

## · Additional information:

EUH066 *Repeated exposure may cause skin dryness or cracking.*

## · 2.3 Other hazards

## · Results of PBT and vPvB assessment

· PBT: Not applicable.  
· vPvB: Not applicable.

**SECTION 3: Composition/information on ingredients**

## · 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

## · Dangerous components:

CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49-xxxx	acetone ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	25-50%
CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37-xxxx	dimethyl ether ⚠ Flam. Gas 1, H220 Press. Gas C, H280	12.5-20%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29-xxxx	n-butyl acetate ⚠ Flam. Liq. 3, H226 ⚠ STOT SE 3, H336	12.5-20%

(Contd. on page 3)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 18.05.2016

Version number 1

Revision: 18.05.2016

**Trade name: ProXL® PLASTICOLOUR AEROSOL TRAFFIC BLACK 400 ML**

(Contd. of page 2)

CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-xxxx	propane ----- Flam. Gas 1, H220 Press. Gas C, H280	5-10%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29-xxxx	2-methoxy-1-methylethyl acetate ----- Flam. Liq. 3, H226	5-10%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32-xxxx	butane ----- Flam. Gas 1, H220 Press. Gas C, H280	5-10%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27-xxxx	isobutane ----- Flam. Gas 1, H220 Press. Gas C, H280	5-10%
CAS: 9004-70-0	Nitrocellulose (nitrogen content <12.6%) ----- Flam. Sol. 1, H228	1-2.5%
CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6 Reg.nr.: 01-2119484630-38-xxxx	butan-1-ol ----- Flam. Liq. 3, H226 Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	1-2.5%
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25-xxxx	propan-2-ol ----- Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	1-2.5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

#### SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

#### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

-GB-

(Contd. on page 4)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 18.05.2016

Version number 1

Revision: 18.05.2016

Trade name: ProXL® PLASTICOLOUR AEROSOL TRAFFIC BLACK 400 ML

(Contd. of page 3)

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Ensure adequate ventilation  
Keep away from ignition sources.
- **6.2 Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**  
Do not spray onto a naked flame or any incandescent material.  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store in a cool location.  
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Protect from heat and direct sunlight.
- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

#### · 8.1 Control parameters

- **Ingredients with limit values that require monitoring at the workplace:**

#### 67-64-1 acetone

WEL	Short-term value: 3620 mg/m <sup>3</sup> , 1500 ppm Long-term value: 1210 mg/m <sup>3</sup> , 500 ppm
-----	--

#### 115-10-6 dimethyl ether

WEL	Short-term value: 958 mg/m <sup>3</sup> , 500 ppm Long-term value: 766 mg/m <sup>3</sup> , 400 ppm
-----	---

#### 123-86-4 n-butyl acetate

WEL	Short-term value: 966 mg/m <sup>3</sup> , 200 ppm Long-term value: 724 mg/m <sup>3</sup> , 150 ppm
-----	---

#### 108-65-6 2-methoxy-1-methylethyl acetate

WEL	Short-term value: 548 mg/m <sup>3</sup> , 100 ppm Long-term value: 274 mg/m <sup>3</sup> , 50 ppm
Sk	

(Contd. on page 5)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.05.2016

Version number 1

Revision: 18.05.2016

**Trade name: ProXL® PLASTICOLOUR AEROSOL TRAFFIC BLACK 400 ML**

(Contd. of page 4)

**106-97-8 butane**

WEL Short-term value: 1810 mg/m<sup>3</sup>, 750 ppm  
 Long-term value: 1450 mg/m<sup>3</sup>, 600 ppm  
 Carc (if more than 0.1% of buta-1.3-diene)

**71-36-3 butan-1-ol**

WEL Short-term value: 154 mg/m<sup>3</sup>, 50 ppm  
 Sk

**67-63-0 propan-2-ol**

WEL Short-term value: 1250 mg/m<sup>3</sup>, 500 ppm  
 Long-term value: 999 mg/m<sup>3</sup>, 400 ppm

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
 Immediately remove all soiled and contaminated clothing  
 Wash hands before breaks and at the end of work.  
 Do not inhale gases / fumes / aerosols.  
 Avoid contact with the eyes.  
 Avoid contact with the eyes and skin.

· **Respiratory protection:** Not required.· **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
 Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/  
 the chemical mixture.

· **Material of gloves:** Not required.· **Penetration time of glove material:** Not required.· **Eye protection:**

Tightly sealed goggles

### SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**· **General Information**· **Appearance:**

**Form:** Aerosol  
**Colour:** Dark grey  
**Odour:** Characteristic  
**Odour threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

**Melting point/Melting range:** Undetermined.  
**Boiling point/Boiling range:** Not applicable, as aerosol.

· **Flash point:** <0 °C (<32 °F)  
 Not applicable, as aerosol.

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 240 °C (464 °F)

(Contd. on page 6)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 18.05.2016

Version number 1

Revision: 18.05.2016

Trade name: ProXL® PLASTICOLOUR AEROSOL TRAFFIC BLACK 400 ML

(Contd. of page 5)

· <b>Decomposition temperature:</b>	Not determined.
· <b>Self-igniting:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· <b>Explosion limits:</b>	
<b>Lower:</b>	1.2 Vol %
<b>Upper:</b>	26.2 Vol %
· <b>Vapour pressure at 20 °C (68 °F):</b>	4000 hPa (3000 mm Hg)
· <b>Density at 20 °C (68 °F):</b>	0.761 g/cm <sup>3</sup> (6.351 lbs/gal)
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not applicable.
· <b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	88.5 %
· <b>EU-VOC:</b>	673.2 g/l
· <b>EU-VOC in %:</b>	88.46 %
· <b>Solids content:</b>	11.3 %
· <b>9.2 Other information</b>	No further relevant information available.

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

**67-64-1 acetone**

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rabbit)
Inhalative	LC50 / 4 h	39 mg/m <sup>3</sup> (rat)

**115-10-6 dimethyl ether**

Inhalative	LC50 / 4 h	308 mg/m <sup>3</sup> (rat)
------------	------------	-----------------------------

(Contd. on page 7)

GB



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 18.05.2016

Version number 1

Revision: 18.05.2016

Trade name: ProXL® PLASTICOLOUR AEROSOL TRAFFIC BLACK 400 ML

(Contd. of page 6)

<b>123-86-4 n-butyl acetate</b>		
Oral	LD50	10770 mg/kg (rat)
Dermal	LD50	>17600 mg/kg (rabbit)
Inhalative	LC50 / 4 h	>21.0 mg/m <sup>3</sup> (rat)
<b>108-65-6 2-methoxy-1-methylethyl acetate</b>		
Oral	LD50	8532 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
Inhalative	LC50 / 4 h	35.7 mg/m <sup>3</sup> (rat)
<b>106-97-8 butane</b>		
Inhalative	LC50 / 4 h	658000 mg/m <sup>3</sup> (rat)
<b>71-36-3 butan-1-ol</b>		
Oral	LD50	2292 mg/kg (rat)
Dermal	LD50	3430 mg/kg (rabbit)
Inhalative	LC50 / 4 h	17.76 mg/m <sup>3</sup> (rat)
<b>67-63-0 propan-2-ol</b>		
Oral	LD50	5045 mg/kg (rat)
Dermal	LD50	12800 mg/kg (rabbit)
Inhalative	LC50 / 4 h	30 mg/m <sup>3</sup> (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**  
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

### · 12.1 Toxicity

· <b>Aquatic toxicity:</b>	
<b>67-64-1 acetone</b>	
EC50 / 48 h	8800 mg/l (daphnia magna)
LC50 / 48 h	2262 mg/l (daphnia magna)
LC50 / 96 h (static)	5540 mg/l (fish)
<b>115-10-6 dimethyl ether</b>	
EC50 / 48 h	>4000 mg/l (daphnia magna)
<b>123-86-4 n-butyl acetate</b>	
EC50 / 48 h	44 mg/l (daphnia magna)
EC50 / 96 h	320 mg/l (algae)
LC50 / 24 h	205 mg/l (daphnia magna)
LC50 / 96 h	18 mg/l (Pimephales promelas)
<b>108-65-6 2-methoxy-1-methylethyl acetate</b>	
EC50	408 mg/l (daphnia magna)

(Contd. on page 8)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 18.05.2016

Version number 1

Revision: 18.05.2016

Trade name: ProXL® PLASTICOLOUR AEROSOL TRAFFIC BLACK 400 ML

(Contd. of page 7)

**71-36-3 butan-1-ol**

EC50 / 48 h	1328 mg/l (daphnia magna)
EC50 / 72 h	8500 mg/l (algae)
LC50 / 96 h	1376 mg/l (Pimephales promelas)

**67-63-0 propan-2-ol**

EC50 / 48 h	13299 mg/l (daphnia magna)
LC50 / 96 h (dynamic)	4200 mg/l (fish)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

**SECTION 13: Disposal considerations**

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
15 01 04	metallic packaging

- **Uncleaned packaging:**
- **Recommendation:** Non contaminated packagings may be recycled.

**SECTION 14: Transport information**

- **14.1 UN-Number**
- **ADR, IMDG, IATA** UN1950
- **14.2 UN proper shipping name**
- **ADR** 1950 AEROSOLS
- **IMDG** AEROSOLS
- **IATA** AEROSOLS, flammable

· **14.3 Transport hazard class(es)**· **ADR**

- **Class** 2 5F Gases.

(Contd. on page 9)

GB



**Safety data sheet**  
according to 1907/2006/EC, Article 31


Printing date 18.05.2016

Version number 1

Revision: 18.05.2016

Trade name: ProXL® PLASTICOLOUR AEROSOL TRAFFIC BLACK 400 ML

(Contd. of page 8)

· <b>Label</b>	2.1
· <b>IMDG, IATA</b>	
	
· <b>Class</b>	2.1
· <b>Label</b>	2.1
· <b>14.4 Packing group</b> · <b>ADR, IMDG, IATA</b>	Void
· <b>14.5 Environmental hazards:</b> · <b>Marine pollutant:</b>	No
· <b>14.6 Special precautions for user</b> · <b>Danger code (Kemler):</b> · <b>EMS Number:</b> · <b>Stowage Code</b>	Warning: Gases. - F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· <b>Segregation Code</b>	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>ADR</b> · <b>Limited quantities (LQ)</b> · <b>Excepted quantities (EQ)</b>	1L Code: E0 Not permitted as Excepted Quantity
· <b>Transport category</b> · <b>Tunnel restriction code</b>	2 D
· <b>IMDG</b> · <b>Limited quantities (LQ)</b> · <b>Excepted quantities (EQ)</b>	1L Code: E0 Not permitted as Excepted Quantity
· <b>UN "Model Regulation":</b>	UN 1950 AEROSOLS, 2.1

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P3a** FLAMMABLE AEROSOLS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

(Contd. on page 10)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 18.05.2016

Version number 1

Revision: 18.05.2016

**Trade name: ProXL® PLASTICOLOUR AEROSOL TRAFFIC BLACK 400 ML**

(Contd. of page 9)

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Relevant phrases**

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H228 Flammable solid.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.

· **Department issuing SDS:** R&D legislation and regulatory advisor

· **Contact:** QHSE Department

· **Abbreviations and acronyms:**

- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
  - IMDG: International Maritime Code for Dangerous Goods
  - IATA: International Air Transport Association
  - GHS: Globally Harmonised System of Classification and Labelling of Chemicals
  - EINECS: European Inventory of Existing Commercial Chemical Substances
  - ELINCS: European List of Notified Chemical Substances
  - CAS: Chemical Abstracts Service (division of the American Chemical Society)
  - LC50: Lethal concentration, 50 percent
  - LD50: Lethal dose, 50 percent
  - PBT: Persistent, Bioaccumulative and Toxic
  - vPvB: very Persistent and very Bioaccumulative
  - DNEL: Derived No-Effect Level (REACH)
  - PNEC: Predicted No-Effect Concentration (REACH)
  - SVHC: Substances of Very High Concern
  - Flam. Gas 1: Flammable gases – Category 1
  - Aerosol 1: Aerosols – Category 1
  - Press. Gas C: Gases under pressure – Compressed gas
  - Flam. Liq. 2: Flammable liquids – Category 2
  - Flam. Liq. 3: Flammable liquids – Category 3
  - Flam. Sol. 1: Flammable solids – Category 1
  - Acute Tox. 4: Acute toxicity – Category 4
  - Skin Irrit. 2: Skin corrosion/irritation – Category 2
  - Eye Dam. 1: Serious eye damage/eye irritation – Category 1
  - Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
  - STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- **\* Data compared to the previous version altered.**

GB