

**Section 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

**Product name:** PROWHEEL - SMART SYSTEM WHEEL BASECOAT COLOUR

**Product code:** SWSXX

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**1.3. Details of the supplier of the safety data sheet**

**Company name:** PROXL  
SECOND AVENUE  
CHATHAM  
KENT  
ME4 5AU  
ENGLAND  
**Tel:** 01634 823900  
**Fax:** 01634 813807  
**Email:** sales@capellasolutionsgroup.com

**1.4. Emergency telephone number**

**Emergency tel:** 01634 823900  
(office hours only)

**Section 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification under CLP:** STOT SE 3: H336; Aquatic Chronic 3: H412; Eye Dam. 1: H318; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT SE 3: H335

**Most important adverse effects:** Flammable liquid and vapour. Causes skin irritation. Causes serious eye damage. May cause respiratory irritation. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects.

**2.2. Label elements**

**Label elements:**

**Hazard statements:** H226: Flammable liquid and vapour.  
H315: Causes skin irritation.  
H318: Causes serious eye damage.  
H335: May cause respiratory irritation.  
H336: May cause drowsiness or dizziness.  
H412: Harmful to aquatic life with long lasting effects.

**Hazard pictograms:** GHS02: Flame

# SAFETY DATA SHEET

PROWHEEL - SMART SYSTEM WHEEL BASECOAT COLOUR

Page: 2

GHS05: Corrosion

GHS07: Exclamation mark



**Signal words:** Danger

**Precautionary statements:** P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241: Use explosion-proof electrical/ventilating/lighting/.. equipment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+352: IF ON SKIN: Wash with plenty of water/.

P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

## 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

##### N-BUTYL ACETATE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
204-658-1	123-86-4	-	Flam. Liq. 3: H226; STOT SE 3: H336; -: EUH066	50-70%

##### LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.

265-199-0	64742-95-6	-	Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H335; Aquatic Chronic 2: H411	1-10%
-----------	------------	---	---	-------

##### BUTAN-1-OL

200-751-6	71-36-3	-	Flam. Liq. 3: H226; Acute Tox. 4: H302; STOT SE 3: H335; Skin Irrit. 2: H315; Eye Dam. 1: H318; STOT SE 3: H336	1-10%
-----------	---------	---	---	-------

##### XYLENE A

905-562-9	-	-	Acute Tox. 4: H312+332; Skin Irrit. 2: H315; STOT RE 2: H373; Flam. Liq. 3: H226; Eye Irrit. 2: H319; Asp. Tox. 1: H304; Acute Tox. 4: H332	1-10%
-----------	---	---	--	-------

[cont...]

## SAFETY DATA SHEET

PROWHEEL - SMART SYSTEM WHEEL BASECOAT COLOUR

Page: 3

### 2-METHYLPROPAN-1-OL

201-148-0	78-83-1	-	Flam. Liq. 3: H226; STOT SE 3: H335; Skin Irrit. 2: H315; Eye Dam. 1: H318; STOT SE 3: H336	1-10%
-----------	---------	---	---	-------

### ETHYLBENZENE

202-849-4	100-41-4	-	Flam. Liq. 2: H225; Acute Tox. 4: H332; STOT RE 2: H373; Asp. Tox. 1: H304	1-10%
-----------	----------	---	---	-------

### LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY

265-150-3	64742-48-9	-	Asp. Tox. 1: H304; Flam. Liq. 3: H226	<1%
-----------	------------	---	---------------------------------------	-----

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

**Ingestion:** Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Eye bathing equipment should be available on the premises.

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

[cont...]

# SAFETY DATA SHEET

PROWHEEL - SMART SYSTEM WHEEL BASECOAT COLOUR

Page: 4

## 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Avoid the formation or spread of mists in the air.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed.

### 7.3. Specific end use(s)

**Specific end use(s):** No data available.

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Hazardous ingredients:**

**N-BUTYL ACETATE**

**Workplace exposure limits:**

**Respirable dust**

State	Workplace exposure limits		Respirable dust	
	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	724 mg/m <sup>3</sup>	966 mg/m <sup>3</sup>	-	-

[cont...]

# SAFETY DATA SHEET

PROWHEEL - SMART SYSTEM WHEEL BASECOAT COLOUR

Page: 5

## BUTAN-1-OL

UK	-	154 mg/m <sup>3</sup>	-	-
----	---	-----------------------	---	---

## ETHYLBENZENE

UK	441 mg/m <sup>3</sup>	552 mg/m <sup>3</sup>	-	-
----	-----------------------	-----------------------	---	---

### DNEL/PNEC Values

**DNEL / PNEC** No data available.

### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Protective gloves.

**Eye protection:** Tightly fitting safety goggles. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Liquid

**Colour:** Various

**Odour:** Characteristic odour

**Evaporation rate:** Slow

**Oxidising:** Non-oxidising (by EC criteria)

**Solubility in water:** Insoluble

**Also soluble in:** Most organic solvents.

**Viscosity:** Viscous

**Boiling point/range°C:** No data available.

**Flammability limits %: lower:** No data available.

**Flash point°C:** 23 - 60

**Autoflammability°C:** No data available.

**Relative density:** 1.025 kg/l

**VOC g/l:** 753 g/l

**Melting point/range°C:** No data available.

**upper:** No data available.

**Part.coeff. n-octanol/water:** No data available.

**Vapour pressure:** No data available.

**pH:** No data available.

### 9.2. Other information

**Other information:** No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

[cont...]

# SAFETY DATA SHEET

PROWHEEL - SMART SYSTEM WHEEL BASECOAT COLOUR

Page: 6

## 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions.

## 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.  
Decomposition may occur on exposure to conditions or materials listed below.

## 10.4. Conditions to avoid

**Conditions to avoid:** Heat.

## 10.5. Incompatible materials

**Materials to avoid:** Strong oxidising agents. Strong acids.

## 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

#### Hazardous ingredients:

##### N-BUTYL ACETATE

ORL	MUS	LD50	6	gm/kg
ORL	RAT	LD50	10768	mg/kg

##### LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.

ORL	RAT	LD50	8400	mg/kg
-----	-----	------	------	-------

##### BUTAN-1-OL

IVN	RAT	LD50	310	mg/kg
ORL	MUS	LD50	2680	mg/kg
ORL	RAT	LD50	790	mg/kg

##### ETHYLBENZENE

IPR	MUS	LD50	2624	µl/kg
ORL	RAT	LD50	3500	mg/kg

#### Relevant hazards for substance:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated

[cont...]

# SAFETY DATA SHEET

PROWHEEL - SMART SYSTEM WHEEL BASECOAT COLOUR

Page: 7

STOT-single exposure

INH

Hazardous: calculated

## Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

## Section 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity values:** No data available.

### 12.2. Persistence and degradability

**Persistence and degradability:** Biodegradable.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No bioaccumulation potential.

### 12.4. Mobility in soil

**Mobility:** Readily absorbed into soil.

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

**Other adverse effects:** Negligible ecotoxicity.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

### 14.1. UN number

**UN number:** UN1263

### 14.2. UN proper shipping name

**Shipping name:** PAINT RELATED MATERIAL

[cont...]

# SAFETY DATA SHEET

PROWHEEL - SMART SYSTEM WHEEL BASECOAT COLOUR

Page: 8

## 14.3. Transport hazard class(es)

Transport class: 3

## 14.4. Packing group

Packing group: III

## 14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

## 14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 3

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

### 15.2. Chemical Safety Assessment

## Section 16: Other information

### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** EUH066: Repeated exposure may cause skin dryness or cracking.

H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H302: Harmful if swallowed.

H304: May be fatal if swallowed and enters airways.

H312+332: Harmful in contact with skin or if inhaled.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

[cont...]



## **SAFETY DATA SHEET**

PROWHEEL - SMART SYSTEM WHEEL BASECOAT COLOUR

**Page: 9**

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.